

Terminations & Loads (Coaxial)

FEATURES:

- ❖ Frequency Range: DC-18GHz
- ❖ Low VSWR
- ❖ Power Rating: 1-1000W
- ❖ Rugged Construction



CCL Series

SPECIFICATIONS:

SQUARE

Model No.	Frequency Range (GHz)	VSWR (Max)	Power (W)	Size LXWXH (mm)	Connector Type
CCLDC0210S	DC-2.0	1.15	10	70X32X32	N
CCLDC0230S	DC-2.0	1.10	30	65X70X70	N
CCLDC02100T	DC-2.0	1.20	100	76X86X215	N
CCLDC02150T	DC-2.0	1.20	150	115X86X262	N
CCLDC02200T	DC-2.0	1.20	200	115X86X262	N
CCLDC02250T	DC-2.0	1.20	250	132X140X337	N
CCLDC02300T	DC-2.0	1.20	300	132X140X337	N
CCLDC02400T	DC-2.0	1.20	400	132X140X422	N
CCLDC02500T	DC-2.0	1.20	500	132X140X422	N
CCLDC021000T	DC-2.0	1.20	1000	152X260X647	N
CCLDC0305S	DC-3.0	1.20	5	-	N
CCLDC0310S	DC-3.0	1.20	10	70X32X32	N
CCLDC0320S	DC-3.0	1.20	20	-	N
CCLDC0325S	DC-3.0	1.20	25	-	N
CCLDC0330S	DC-3.0	1.20	30	-	N
CCLDC0350S	DC-3.0	1.20	50	-	N
CCLDC03100S	DC-3.0	1.20	100	-	N
CCLDC03200S	DC-3.0	1.20	200	-	N
CCLDC0405S	DC-4.0	1.35	5	-	N
CCLDC0410S	DC-4.0	1.35	10	-	N
CCLDC0420S	DC-4.0	1.35	20	-	N
CCLDC0425S	DC-4.0	1.35	25	-	N

Terminations & Loads (Coaxial)

Model No.	Frequency Range (GHz)	VSWR (Max)	Power (W)	Size LXWXH (mm)	Connector Type
CCLDC0430S	DC-4.0	1.35	30	-	N
CCLDC0450S	DC-4.0	1.35	50	-	N
CCLDC04100S	DC-4.0	1.35	100	-	N
CCLDC04150S	DC-4.0	1.35	150	-	N
CCLDC04200S	DC-4.0	1.35	200	-	N
CCLDC0425T	DC-4.0	1.15	25	44x69	N-M
CCLDC04250T	DC-4.0	1.35	250	132X140X337	N
CCLDC04300T	DC-4.0	1.35	300	132X140X337	N
CCLDC04400T	DC-4.0	1.35	400	132X140X422	N
CCLDC04500T	DC-4.0	1.35	500	132X140X422	N
CCLDC041000T	DC-4.0	1.35	1000	152X260X647	N
CCLDC0850	DC-8.5	1.2	50	-	SMA/N
CCLDC1025T	DC-10	1.25	25	44x69	N-M
CCLDC1025	DC-10	1.2	25	-	SMA/N
CCLDC1805	DC-18	1.2	5	-	SMA/N
CCLDC1810	DC-18	1.2	10	-	SMA/N
CCLDC1825	DC-18	1.2	25	-	SMA/N
CCLDC1850	DC-18	1.2	50	-	SMA/N
CCLDC18100	DC-18	1.2	100	-	SMA/N
CCLDC18150	DC-18	1.50	150	-	SMA/N
CCLDC2605	DC-26.5	1.35	5	-	2.92mm-M
CCLDC2610	DC-26.5	1.35	10	-	3.5mm-M
CCLDC2625	DC-26.5	1.35	25	-	3.5mm-M
CCLDC4005	DC-40	1.35	5	-	2.92mm-M
CCLDC50U5	DC-50	1.35	0.5	-	2.4mm-M
CCLDC65U5F	DC-65	1.35 Typ.	0.5	-	1.8mm-F
CCLDC65U5M	DC-65	1.35 Typ.	0.5	-	1.8mm-M
CCLDC110U5F	DC-110	1.50	0.5	2.2 X 0.8 cm (Length x Diameter)	1mm-F
CCLDC110U5M	DC-110	1.33	0.5	2.5 X 0.8 cm (Length x Diameter)	1mm-M

TUBULAR:



Terminations & Loads (Coaxial)

Model No.	Frequency Range (GHz)	VSWR (Max)	Power (W)	Size LXWXH (mm)	Connector Type
CCLDC0305S	DC-3.0	1.20	5	Φ19 X 30	N
Model No.	Frequency Range (GHz)	VSWR (Max)	Power (W)	Size LXWXH (mm)	Connector Type
CCLDC0405S	DC-4.0	1.35	5	-	N
CCLDC0410S	DC-4.0	1.35	10	-	N
CCLDC0420S	DC-4.0	1.35	20	-	N
CCLDC0425S	DC-4.0	1.35	25	-	N
CCLDC0430S	DC-4.0	1.35	30	-	N
CCLDC0450S	DC-4.0	1.35	50	-	N
CCLDC0402T1	DC-4.0	1.35	5	-	N
CCLDC0402T2	DC-4.0	1.35	5	-	N
CCLDC0403T	DC-4.0	1.15	3	Φ26 X 39	N
CCLDC0450T1	DC-4.0	1.15	50	Φ50 X 100	N
CCLDC0450T2	DC-4.0	1.35	50	Φ50 X 100	N
CCLDC0610T	DC-6.0	1.15	10	Φ32 X 60	N
CCLDC0615T	DC-6.0	1.20	15	Φ35 X 64	N
CCLDC0625T	DC-6.0	1.20	25	Φ40 X 64	N
CCLDC0630T	DC-6.0	1.20	30	Φ40 X 64	N
CCLDC1202T1	DC-12.4	1.12	2	Φ21 X 44	N
CCLDC1202T2	DC-12.4	1.15	2	Φ14 X 24	SMA
CCLDC1205T	DC-12.4	1.30	5	Φ27 X 52	N
CCLDC1215T	DC-12.4	1.30	15	Φ35 X 64	N
CCLDC1225T	DC-12.4	1.30	25	Φ40 X 64	N
CCLDC1250T	DC-12.4	1.25	50	Φ50 X 100	N
CCLDC1801	DC-18.0	1.20	1	-	SMA-M
CCLDC1802	DC-18.0	1.20	2	-	SMA-M
CCLDC26U5	DC-26.5	1.20	0.5	-	SMA-M
CCLDC2601	DC-26.5	1.20	1	-	SMA-M
CCLDC4001	DC-40	1.35	1	-	2.92mm-M
CCLDC4002	DC-40	1.35	2	-	2.92mm-M

OTHER FREQUENCIES AND POWER LEVELS ARE ALSO AVAILABLE.

CERNEX RESERVE THE RIGHT TO CHANGE THE SPECIFICATIONS WITHOUT NOTICE